




Sailfish 236 CC - Performance Bulletin

Motors: Single Yamaha F250XCA

PERFORMANCE				
RPM	MPH	GPH	MPG	
1000	5.0	1.2	4.17	
1500	6.2	1.8	3.42	
2000	8.3	3.3	2.50	
2500	9.1	5.2	1.77	
3000	10.9	6.7	1.62	
3500	13.9	9.1	1.53	
4000	29.2	11.5	2.55	
4500	34.1	14.1	2.43	
5000	38.2	19.0	2.01	
5500	41.7	23.1	1.81	
6000	45.5	25.1	1.81	
ACCELERATON				
0-30MPH - 9.50 Sec.				
TEST CONDITIONS				
NUMBER OF PEOPLE			3	
AIR TEMP (Fahrenheit)			80° F/74° F	
ELEVATION (IN FEET ABOVE SEA LEVEL)			174'	
WIND VELOCITY			5 ~ 10 MPH	



NAME: Sailfish Boats	MANUFACTURER INFO			
CITY, STATE, ZIP: Cairo, GA 39828 PHONE: 229-377-2125 FAX: 229-377-1855 WEBSITE: www.sailfishboats.com BOAT MODEL LENGTH 23' 6" BEAM 8' 6" APROX WET WEIGHT 5400 lbs MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE DETAILS ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	NAME:	Sailfish Boats		
PHONE: 229-377-2125 FAX: 229-377-1855 WEBSITE: www.sailfishboats.com BOAT MODEL 236CC LENGTH 23' 6" BEAM 8' 6" APROX WET WEIGHT 5400 lbs MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	STREET:	PO Box 1899		
FAX: 229-377-1855 WEBSITE: www.sailfishboats.com BOAT DETAILS BOAT MODEL 236CC LENGTH 23' 6" BEAM 8' 6" APROX WET WEIGHT 5400 lbs MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE DETAILS ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	CITY, STATE, ZIP:	Cairo, GA 39828		
WEBSITE: www.sailfishboats.com BOAT DETAILS BOAT MODEL 236CC LENGTH 23' 6" BEAM 8' 6" APROX WET WEIGHT 5400 lbs MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE DETAILS ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	PHONE:	229-377-2125		
BOAT DETAILS	FAX:	229-377-1855		
BOAT MODEL 236CC LENGTH 23' 6" BEAM 8' 6" APROX WET WEIGHT 5400 lbs MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	WEBSITE:	www.sailfishboats.com		
LENGTH 23' 6" BEAM 8' 6" APROX WET WEIGHT 5400 lbs MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE DETAILS ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	BOAT DETAILS			
BEAM 8' 6" APROX WET WEIGHT 5400 lbs MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE DETAILS ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	BOAT MODEL	236CC		
APROX WET WEIGHT 5400 lbs MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE DETAILS ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	LENGTH	23' 6"		
MAXIMUM HP 300 Hp FUEL CAPACITY 110 Gal ENGINE DETAILS ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	BEAM	8' 6"		
FUEL CAPACITY 110 Gal ENGINE DETAILS ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	APROX WET WEIGHT	5400 lbs		
ENGINE DETAILS	MAXIMUM HP	300 Hp		
ENGINE MODEL/S F250XCA HORSEPOWER 250 HP INDUCTION EFI/VCT/DOHC DISPLACEMENT 4.2 L WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	FUEL CAPACITY	110 Gal		
HORSEPOWER	ENGINE DETAILS			
INDUCTION	ENGINE MODEL/S	F250XCA		
DISPLACEMENT	HORSEPOWER	250 HP		
WEIGHT 562 lbs GEAR RATIO 1.75:1 ENGINE MOUNTING HEIGHT MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	INDUCTION	EFI/VCT/DOHC		
GEAR RATIO	DISPLACEMENT	4.2 L		
ENGINE MOUNTING HEIGHT	WEIGHT	562 lbs		
MOUNTING HOLE POSITION #3 PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	GEAR RATIO	1.75:1		
PROPELLER/S SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	ENGINE MOUNTING HEIGHT			
SERIES SALTWATER SERIES II / SDS HUB DIAMETER/PITCH 15 3/4 x 15	MOUNTING HOLE POSITION	#3		
DIAMETER/PITCH 15 3/4 x 15	PROPELLER/S			
	SERIES	SALTWATER SERIES II / SDS HUB		
YAMAHA PART # (sql) 6CF-45976-00-00	DIAMETER/PITCH	15 3/4 x 15		
174WATAT AKT # (391) 00L-43910-00-00	YAMAHA PART # (sgl)	6CE-45976-00-00		
PROPELLER MATERIAL POLISHED STAINLESS STEEL	PROPELLER MATERIAL	POLISHED STAINLESS STEEL		
COMMENTS				

BOAT EQUIPPED WITH TWO BATTERIES, T-TOP, FULL TANK OF FUEL, THREE PERSONS, MISC. SAFETY AND TEST GEAR (APPROX 180 LBS)

Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Seminole Marine Inc. reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice.

DEMAND THE DIFFERENCE